## Baton Security Products, Inc

11521 Salinaz Avenue, Garden Grove, California 92843, USA Tel:(714) 590 6969 Fax:(714) 590 6960 Email address: Sales@batonlockusa.com



Form QF-E10	Quotation	Ref#		How to identif	fv mv Furo M	ortise Lock Case
	Order	PO#		TOW to lucitui	y iliy Luio ivi	UTIISO LUUN OUSO
Brand name if you have:  Center of cylinder /Leve	Dear Ba  If you kr  the draw  to us so	ving to th	t your lock is so he left, please fi	ill out the follow	ring questions f	s a profile cylinder as rom 1 to 10 and return ur replacement.
Lever		Name_ Add				
Euro Profi Cylinder	info	_				
	a sa	-			State	Zip
door thickness exterior interior		Tel: _				
	_ \ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\	Email :				
Mark here only if need new cylinder    Mark here only if need new cylinder						
Size of Faceplate				re the size o lare steel ba		r Spindle / o the Lever)
<b>W</b> / Width=mm			∠	m on square	• (ot	her size/specify)
H / Height= mm			8mı	m on square	, <u> </u>	
4 Finish/color	atch	ツ   	E the	to <b>C</b> /Measu Center of t	ure the distant	ance between nd Cylinder
of Faceplate Brass		C to	C 72m	m 🔲 85r	nm	(other /specify)
	Hole for Cylind		92m		ōmm	
	tig	70	Backs	Measure the cedge to center	distance from the r of the Cylinder/L	door ever.
Finish/color of Deadbolt / Latch	Deadbolt		25mm	( 1" )	5mm( 1-3/4")	65mm( 2-9/16")
☐ Brass			30mm(	(1-3/16") 5	50mm( 2" )	70mm( 2-3/4" )
	© Backset				55mm( 2-3/16")	80mm( 3-1/8" )
Lock function:	-	<u> </u>	40mm(	(1-9/16") 6	60mm( 2-3/8")	100mm(3-15/16")
When Deadbolt is thrown/locke	ea,   <del> </del>	case	e model #	Unit Price	Rer	narks
by operating the Lever only.  When Deadbolt is thrown/lock from inside I must unlock the Deadbolt by cylinder and then operate the Lever to open the					_	